

4330 S. Johnson Rd Chanute KS 66720 www.popuphitch.com

### **Installation Instructions**

## Model RVGC- ADJ

**RVGC-4205A** 

Fits Lippert 1621 & 0719

**RVGC-4210A** 

Fits Lippert 1716, 1116 & 0115



# Model RVGC 8-2013



**Model Number RVGC** 

Gross Trailer Weight: 24,000 lbs

Gross Trailer Tounge Weight: 6,500 lbs

#### **INSTALLATION PROCEDURE**

WARNING: Verify adequate trailer swing clearance between trailer nose and cab of truck.

- 1. Simply remove your existing king pin box and install the RVGC-ADJ back in the same location on your camper.
- **2.** Attach the angled "L" bracket on the outside of the unit behind one of the bolts that attach the RVGC-ADJ to the camper.
- **3.** Place the pull cable thru the slot in the angled "L" bracket and run it to the round hole in the end of the coupler handle and attach with the provided 3/8" X 1" Hex Bolt and Nut.
- **4.** To adjust height simply loosen the 1/2" X1" set bolt in the back of the down tube. Then remove the 3/4" X 5" Bent Pin with keeper. Move lower portion to desired postion, Re-Install Bent Pin with keeper and tighten set bolt.
- 5. Torque Pin Box Fastners to 120 ft pounds.

### Hardware Provided

1pcs- 1/2"-X1" Set bolt

1pcs- 1/2" Nut

1pcs- 3/4" X 5" Bent pin with keeper

1pcs- 3/8" X 1" Hex Bolt

1pcs- 3/8" Lock Nut

1pcs- "L" Bracket cable Guide

1pcs- Pull Cable with Handle





Read the SAFE TOWING INSTRUCTIONS on the PopUp Warranty sheet.